



MORE THAN CONCRETE

DRIVEWAY SEALER

IDEAL FOR DOMESTIC DRIVEWAYS, ENTERTAINMENT AREAS AND CONCRETE PATHWAYS
SOLVENT BASED | WATER REPELLENT



AVAILABLE SIZES: 1L, 4L, 20L



SCAN FOR DETAILS



DESCRIPTION:

CEMIX® DRIVEWAY SEALER is a high gloss, solvent based decorative sealer, designed to enhance the colour and texture of concrete surfaces. It will assist in reducing moss and mould by reducing the amount of water that can enter the concrete. It is clear and of low-medium viscosity in appearance, resembling a medicine syrup. CEMIX DRIVEWAY SEALER is a topical (film forming) product which will not deeply penetrate the surface. When correctly applied, it will not yellow, crack or peel and will offer good scratch and abrasion resistance. CEMIX DRIVEWAY SEALER is applied by roller or spray unit and is fast drying - areas being coated can generally be put into service within 1 day of application.

SUITABLE PROJECTS:

Domestic and commercial concrete driveways and patios. Concrete/Coloured concrete/Exposed Aggregate/Paving.

LIMITATIONS:

CEMIX DRIVEWAY SEALER is a decorative product. As with all clear concrete sealers, it will offer a good degree of resistance to water ingress however it must not be considered a fully functioning waterproofing system. For waterproofing please refer to the CEMIX Waterproofing suite of products. CEMIX DRIVEWAY SEALER does not conform to CCANZ CP 01:2014 Code of Practice for Weathertight Concrete and Concrete Masonry Construction.

PREPARATION:

Effective substrate preparation is essential for CEMIX DRIVEWAY SEALER to bond and perform correctly. When sealing new concrete, the surface must be fully cured for a minimum of 28

days before sealing commences. For sealing old concrete, any old coatings must be removed to provide a clean porous surface. Where practical, refer to the manufacturer of the existing coating for the effective removal method or consult CEMIX for advice. All surfaces to be sealed must be free from contamination. Thoroughly clean the area to remove all loose and deleterious materials and debris, including all dust and any dirt, grease, organics, form release or curing agents and oil.

MIXING:

CEMIX DRIVEWAY SEALER is used straight from the tin. Stir thoroughly before use. A diluted first coat by way of the addition of mineral turpentine can be used if desired for more porous surfaces.

APPLICATION:

The surface being sealed must be completely dry. It is recommended that a test area be done first then allowed to dry, to ascertain the level of gloss achieved per coat. In general, 2 coats are recommended, however some porous concretes may require 3 coats to achieve an adequate build. The time between coats will vary depending on temperatures, however a minimum 4 hours is recommended. To test for drying off, place a finger on a small inconspicuous area. No fingerprint impression should be left on the surface. Regardless of using a roller or spray unit, apply as if it were a paint, using even strokes in one direction. Never apply more product than is being absorbed into the surface you are sealing. If product is pooling on the surface, disperse the excess with a roller.

NOTE: Before applying any sealer on a fresh concrete, ensure a minimum of 28 days for curing.



Scan to see Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

DRIVEWAY SEALER

CURING:

CEMIX DRIVEWAY SEALER will be tacky whilst drying however will dry rapidly. Each coat will lighten as it dries. In general, areas being coated can be put in to service within 1 day of application, however it is always recommended to allow the product to dry as long as possible.

CLEANING UP:

Clean up with mineral turps or similar solvent.

MAINTAINANCE:

The working life of CEMIX DRIVEWAY SEALER may be affected by weather and vehicle or foot traffic, ranging from a few to several years. Visible signs of reduced sheen or track marks are an indication that a re-coat is necessary. Maintenance re-coating using CEMIX DRIVEWAY SEALER is carried out by cleaning the surface and removing any loose film, followed by a solvent wipe, then application of the fresh sealer over the old. No stripping of the old sealer is required.

SHELF LIFE:

CEMIX DRIVEWAY SEALER can be stored well sealed in its original tin, in a dry place, for a period of 6 months. It must be stored in a safe place away from children.

YIELDS:

* 1L will cover approximately 10m² per coat, depending upon the porosity of the concrete being coated.

Read Label Before Use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

WARNING



HAZARD STATEMENTS:

- Flammable liquid and vapour
- Harmful if swallowed
- Harmful in contact with skin
- May be harmful if inhaled
- Causes skin irritation
- Causes serious eye irritation
- Suspected of damaging fertility or the unborn child
- May cause damage to organs
- May cause damage to organs through prolonged or repeated exposure
- Toxic to aquatic life
- May cause long lasting harmful effects to aquatic life
- Harmful to terrestrial vertebrates

SAFETY INSTRUCTIONS:

- Use personal protective equipment as required
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment
- Use only non-sparking tools
- Wear protective gloves/protective clothing/eye protection/face protection

INGREDIENTS:

Xylene, 1330-20-7, 70 - 75%
Methylacrylate copolymer, (CAS Not Available), 20 - 25%
Ethylene glycol monobutyl ether, 111-76-2, <2%

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION:



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring